

# PSA-RP

## Standard Inverter

## Heat Pump

### Floor Standing System



Our Standard Inverter range offers customers all the features and benefits of inverter technology whilst being cost effective. The PSA-RP Floor Standing System complements the Mitsubishi Electric range of indoor units. The sleek, modern design of this unit is ideal for numerous applications including bars and restaurants.

#### Key Features

- Built in controller

Note: When used with a Mr Slim Multi-Split system PSA-RP cannot be connected with indoor units of different type.



PSA-RP - INDOOR UNITS	PSA-RP100KA	PSA-RP100KA	PSA-RP125KA	PSA-RP125KA	PSA-RP140KA	PSA-RP140KA
CAPACITY (kW)	Heating (nominal)	11.2 (4.5-12.5)	11.2 (4.5-12.5)	14.0 (5.0-16.0)	14.0 (5.0-16.0)	16.0 (5.0-18.0)
	Cooling (nominal)	9.4 (4.9-11.2)	9.4 (4.9-11.2)	12.3 (5.5-14.0)	12.3 (5.5-14.0)	13.6 (5.5-15.0)
	Heating (UK)	9.5 (3.85-10.65)	9.5 (3.85-10.65)	11.9 (4.25-13.6)	11.9 (4.25-13.6)	13.6 (4.25-15.3)
	Cooling (UK)	8.65 (4.5-10.3)	8.65 (4.5-10.3)	11.3 (5.05-12.9)	11.3 (5.05-12.9)	12.5 (5.06-12.7)
SHF (nominal & UK)		0.73	0.73	0.72	0.72	0.71
COP / EER (nominal)		3.41 / 3.01	3.41 / 3.01	2.81 / 2.81	2.81 / 2.81	2.81 / 2.41
SCOP / SEER (BS EN14825)		3.8 / 4.6	3.8 / 4.6	3.7 / 3.5	3.7 / 3.5	3.4 / 3.2
ErP ENERGY EFFICIENCY CLASS	Heating/Cooling	A / B	A / B	N/A	N/A	N/A
AIRFLOW (m³/min)	Lo-Mi-Hi	25-28-30	25-28-30	25-28-31	25-28-31	25-28-31
PIPE SIZE mm (in)	Gas/Liquid	15.88 (5/8") / 9.52 (3/8")	15.88 (5/8") / 9.52 (3/8")	15.88 (5/8") / 9.52 (3/8")	15.88 (5/8") / 9.52 (3/8")	15.88 (5/8") / 9.52 (3/8")
SOUND PRESSURE LEVEL (dBA)	Lo-Mi-Hi	45-49-51	45-49-51	45-49-51	45-49-51	45-49-51
SOUND POWER LEVEL (dBA)		65	65	66	66	66
DIMENSIONS (mm)	Width x Depth x Height (Grille)	600 x 360 x 1900				
WEIGHT (kg)		46	46	46	46	48
ELECTRICAL SUPPLY		Fed by Outdoor Unit				
FUSE RATING (BS88) - HRC (A)		6	6	6	6	6
INTERCONNECTING CABLE No. Cores		4	4	4	4	4

PUHZ-P - OUTDOOR UNITS	PUHZ-P100VHA4	PUHZ-P100YHA2 ③	PUHZ-P125VHA3	PUHZ-P125YHA ③	PUHZ-P140VHA3	PUHZ-P140YHA ③
SOUND PRESSURE LEVEL (dBA) Heating/Cooling	54 / 50	54 / 50	55 / 51	55 / 51	56 / 52	56 / 52
SOUND POWER LEVEL (dBA) Cooling	70	70	71	71	73	73
WEIGHT (kg)	75	77	99	101	99	101
DIMENSIONS (mm)	Width x Depth x Height	950 x 330 + 30 x 943	950 x 330 + 30 x 943	950 x 330 + 30 x 1350	950 x 330 + 30 x 1350	950 x 330 + 30 x 1350
ELECTRICAL SUPPLY		220-240v, 50Hz	380-415v, 50Hz	220-240v, 50Hz	380-415v, 50Hz	220-240v, 50Hz
PHASE	Single	Three	Single	Three	Single	Three
SYSTEM POWER	Heating/Cooling (nominal)	3.280 / 3.120	3.280 / 3.120	4.980 / 4.380	4.980 / 4.380	5.690 / 5.640
INPUT (kW)	Heating/Cooling (UK)	2.92 / 2.65	2.92 / 2.65	4.43 / 3.72	4.43 / 3.72	5.06 / 4.79
STARTING CURRENT (A)		12.0	4.0	15.0	5.0	15.0
SYSTEM RUNNING CURRENT (A)	Heating/Cooling [MAX]	15.36 / 14.69 [28.7]	5.92 / 5.71 [13.7]	17.47 / 18.10 [28.7]	6.82 / 6.91 [13.7]	22.04 / 23.21 [30.2]
FUSE RATING (BS88) - HRC (A)		32	16	32	16	40
MAINS CABLE No. Cores		3	5	3	5	3
MAX PIPE LENGTH (m)		50	50	50	50	50
MAX HEIGHT DIFFERENCE (m)		30	30	30	30	30
CHARGE R410A (kg)		3.0	3.0	4.5	4.5	4.5

③ Three Phase Notes: All units charged to 30m (100-140) pipe length.

## Accessories

### Outdoor Units

#### PAC-SG59SG

Air outlet guide for  
PUHZ-P100-140VHA4(YHA2/VHA3/YHA)

### System Control Units

#### PAC-SA89TA

Remote on/off adaptor

#### PAC-SA88HA

Run/fault adapter

#### PAC-SE41TS

Remote sensor

#### MAC-557IF

MELCloud WiFi interface

#### PAC-SF83MA

A/M-NET adaptor for  
PUHZ-P100-140VHA4(YHA2/VHA3/YHA)


#### PAR-31MAA

Remote controller


## Product Dimensions

PSA-RP100/125/140KA


Upper View



Front View



Side View



Note: additional accessories are available, please see the Optional Extras page at the end of this section for the full range.