



FBQ-C8 / RZQSG Seasonal Classic

Functionality to suit commercial environments



Daikin's concealed ceiling unit is a ducted type fan coil that has been re-engineered for Seasonal Efficiency, combining improved efficiencies in year round conditions with functionality to suit commercial environments.

Quiet, with noise levels as low as 29 decibels, the FBQ-C8 series has a slim profile to allow it to be fitted into narrow ceiling voids. It is able to be connected to flexible duct-work to provide heating and cooling in unusual shaped or long rooms.

Energy savings can be made using the remote controller which gives control over set-point ranges and day-to-day use of controls. The controller can also be connected to an optional wireless temperature sensor to allow give accurate readings of room temperature for better comfort levels.

The Seasonal Classic can be used on existing R22 pipework, making the Concealed ceiling unit ideal for refurbishment projects.



BRC1E52A



RZQSG100L8V1



FBQ-C8



FBQ-C8 / RZQSG

Features	Benefits
R22 Replacement technology	Re-use of existing R22 and R407C piping possible, allowing only fan-coil and condensers to be replaced
D3 connection as standard	Allows integration of split system into Daikin building management systems
Integral drain-pump	Built in pump allows drain-up of 625mm for connection to condensate drain tube in ceiling void
Automatic air-flow adjustment via remote control	Simpler to commission the system and achieve optimum air-flow

Indoor unit			Single Phase				3 Phase					
			FBQ71C8	FBQ100C8	FBQ125C8	FBQ140C8	FBQ100C8	FBQ125C8	FBQ140C8			
Cooling Capacity	Nominal	kW	6.8	9.5	12	13.4	9.5	12	13.4			
	UK Total	kW	7.28	10.8	13.6	14.9	10.8	13.6	14.9			
	UK Sensible	kW	4.99	7.44	9.3	10.25	7.44	9.3	10.25			
Heating Capacity	Nominal	kW	7.5	10.8	13.5	15.5	10.8	13.5	15.5			
Seasonal efficiency (according to EN14825)	Cooling	Energy label	A+			A			-			
		Pdesign	kW	6.8	9.5	12.0	-	9.5	12.0	-	-	
		SEER		5.81	5.50	5.20	-	5.50	5.20	-	-	
	Annual energy consumption		kWh	410	604	807	-	604	807	-	-	
	Heating (Average climate)	Energy label		A			A+			A		
		Pdesign	kW	6.0	7.6			-			7.6	
SCOP			3.88	4.01	3.90	-	4.01	3.90	-	-		
Annual energy consumption		kWh	2,166	2,653	2,728	-	2,653	2,728	-	-		
Nominal efficiency (cooling at 35°/27°)	EER		3.28	3.31	3.21	3.02	3.31	3.21	3.02			
	COP		3.61	3.65	3.51	3.41	3.65	3.51	3.41			
nominal load, heating at 7°/20° nominal load)	Annual energy consumption	kWh	1,037	1,435	1,870	2,220	1,435	1,870	2,220			
	Energy label Cooling/Heating		A/A			A/B			B/B			
Nominal Power Input	Cooling / Heating	kW	2.07 / 2.08	2.87 / 2.96	3.74 / 3.85	4.44 / 4.54	2.87 / 2.96	3.74 / 3.85	4.44 / 4.54			
Dimensions	Height x Width x Depth	mm	300 x 1000 x 700	300 x 1400 x 700			300 x 1400 x 700					
Weight		kg	38	45			45					
Air Flow Rate	High / Low	m ³ /min	18 / 15	32 / 23	39 / 28	39 / 28	32 / 23	39 / 28	39 / 28			
External Static Pressure	High / Nom.	Pascals	100 / 30	120 / 40	120 / 50	120 / 50	120 / 40	120 / 50	120 / 50			
Sound Power	High	dBA	65	69	67	69	69	67	69			
Sound Pressure	High / Low	dBA	37 / 29	38 / 32	40 / 33	40 / 33	38 / 32	40 / 33	40 / 33			
Refrigerant	Type		R410A				R410A					
Power Supply			From outdoor unit				From outdoor unit					
Controller			BRC1E52A wired				BRC1E52A wired					

Outdoor unit			RZQSG71L3V1	RZQSG100L9V1	RZQSG125L9V1	RZQSG140L9V1	RZQSG100L8Y1	RZQSG125L8Y1	RZQSG140LY1
Dimensions	Height x Width x Depth	mm	770 x 900 x 320	990 x 940 x 320		1430 x 940 x 320	990 x 940 x 320		1430 x 940 x 320
Weight		kg	67	81		102	82		101
Operation Range	Cooling Min~Max	°CDB	-15°C to +46°C				-15°C to +46°C		
	Heating Min~Max	°CWB	-15°C to +15.5°C				-15°C to +15.5°C		
Sound Power	High	dBA	65	69	67	69	69	67	69
Sound Pressure	Nom.	dBA	49	53	51	53	53	51	53
Refrigerant	Type		R410A				R410A		
Power Supply			1~ / 50Hz / 220 - 240v				3~ / 50Hz / 400v		
Piping Connections	Liquid (OD)/Gas	inches	3/8 / 5/8				3/8 / 5/8		
Piping Length (Maximum)		m	50	50		50	50		50
Max Installation Height Difference		m	15	30		30	30		30

- Accessories**
- Wireless remote controller (BRC4C65)
 - Wireless room mounted temperature sensor (K.RSS)
 - Decoration grille for return air suction (BYBS71D / BYBS125B)

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com