

INVERTER HEAT PUMP MODEL

FDTC-VF

4way Ceiling Cassette type




Individual flap control system

According to room temperature conditions, four directions of air flow can be controlled by individual flap as preferred. As individual flap control is available even after installation, installation area became wider than before.




Flap control system

Selection of flap position is possible. Individual flaps can be set at different angles.



600mm Drain Pump is mounted

Drain can be discharged upward by 600mm from the ceiling surface close to the indoor unit. It allows a piping layout with a high degree of freedom depending on the installation location.



FDTC25VF, FDTC35VF,
FDTC40VF, FDTC50VF,
FDTC60VF



All FDTC-VF series (except FDTC40VF) can be selected for use as indoor units in the combination with SCM Multi system outdoor unit.

Wired remote control (option)



Wireless remote control (option)





SRC25ZMX-S, SRC35ZMX-S



SRC40ZMX-S, SRC50ZMX-S,
SRC60ZMX-S

Refrigerant pipe length



FDTC25VF, FDTC35VF

FDTC40VF, FDTC50VF
FDTC60VF

FUNCTION



SPECIFICATIONS

| | Indoor unit | FDTC25VF SRC25ZMX-S | FDTC35VF SRC35ZMX-S | FDTC40VF SRC40ZMX-S | FDTC50VF SRC50ZMX-S | FDTC60VF SRC60ZMX-S |
|-------------------------------------|-------------------------|------------------------|------------------------|-----------------------------------|-----------------------------------|---------------------------|
| Outdoor unit | | | | | | |
| Power source | | | | | | 1 Phase, 220 - 240V, 50Hz |
| Nominal cooling capacity (Min~Max) | kW | 2.55 (0.9 ~ 3.2) | 3.6 (0.9 ~ 4.1) | 4.0 (1.1 ~ 4.7) | 5.0 (1.1 ~ 5.6) | 5.6 (1.1 ~ 6.3) |
| Nominal heating capacity (Min~Max) | kW | 3.45 (0.9 ~ 4.7) | 4.25 (0.9 ~ 5.1) | 4.5 (0.6 ~ 5.4) | 5.4 (0.6 ~ 6.3) | 6.7 (0.6 ~ 6.7) |
| Power consumption | Cooling/Heating | kW | 0.6 / 0.84 | 1.07 / 1.16 | 1.04 / 1.10 | 1.56 / 1.45 |
| EER/COP | Cooling/Heating | | 4.25 / 4.11 | 3.36 / 3.66 | 3.85 / 4.09 | 3.21 / 3.72 |
| Inrush current | 220/230/240 V | A | 4.1 / 4.0 / 3.8 | 5.3 / 5.1 / 4.9 | 5.0 | 5.0 |
| Max. running current | | | 9 | 12 | 14 | 14 |
| * Sound power level | Indoor | Cooling/Heating | 56 | 58 | 60 | 60 |
| | Outdoor | Cooling/Heating | 56 | 58 | 63 | 64 |
| * Sound pressure level | Indoor | Cooling (Hi/Me/Lo) | 36 / 32 / 29 | 40 / 36 / 30 | 42 / 36 / 30 | 42 / 36 / 30 |
| | Outdoor | Heating (Hi/Me/Lo) | 38 / 33 / 29.5 | 42 / 35 / 32 | 42 / 36 / 32 | 46 / 39 / 32 |
| Air flow | Indoor | Cooling (Hi/Me/Lo) | 47 / 47 | 50 / 50 | 50 / 50 | 54 / 54 |
| | Indoor | Heating (Hi/Me/Lo) | 9 / 8 / 6.5 | 9.5 / 9 / 7 | 11.5 / 9 / 7 | 13.5 / 10 / 7 |
| | Outdoor | Cooling/Heating | 9.5 / 8.5 / 7 | 10 / 9 / 8 | 11.5 / 9 / 8 | 13.5 / 10 / 8 |
| Exterior dimensions | Indoor | HeightxWidthxDepth | m³/min | 29.5 / 27.0 | 32.5 / 29.5 | 36 / 33 |
| | Outdoor | | | | | |
| Net weight | Indoor / Outdoor | kg | | 595 x 780(+62) x 290 | 640 x 800(+71) x 290 | |
| Ref.piping size | Liquid/Gas | ø mm | | 18.5 (Unit : 15 Panel : 3.5) / 35 | 18.5 (Unit : 15 Panel : 3.5) / 45 | |
| Refrigerant line (one way) length | | m | | 6.35(1/4") / 9.52(3/8") | 6.35(1/4") / 12.7(1/2") | |
| Vertical height differences | Outdoor is higher/lower | m | | Max. 15 | Max. 30 | |
| Outdoor operating temperature range | Cooling | °C | | Max. 10 / Max.10 | Max. 20 / Max.20 | |
| | Heating | | | -15~46 | -15~21 | |
| Clean filter | | | | | TC-PSA-25W-E | |

The data are measured under the following conditions (ISO-T1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

Indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

※ Powerful-Hi can be selected. Sound level dB(A):25VF(Cooling:38 Heating:39), 35VF(Cooling:41 Heating:43), 40/50/60VF(Cooling:47 Heating:47), Airflow m³/min:25VF(Cooling:10 Heating:10.5), 35VF(Cooling:11 Heating:11.5), 40/50/60VF(Cooling:13.5 Heating:13.5)