

INVERTER HEAT PUMP MODEL (High COP)

SRR-ZJ

Ceiling Concealed type



Standard equipment

NEW SRR25ZJ-S, SRR35ZJ-S




SRR25/35ZJ can be selected for use as indoor units in the combination with SCM Multi system outdoor unit.



SRC25ZJX-S, SRC35ZJX-S

Refrigerant pipe length



SRR25ZJ-S
SRR35ZJ-S

OPTIONAL PARTS FOR DUCTED TYPE



FUNCTION



Comfortable Functions



Convenient & Economy Functions



Maintenance & Prevention Functions



Others



SPECIFICATIONS

Model (Indoor unit/Outdoor unit)			SRR25ZJ-S SRC25ZJX-S	SRR35ZJ-S SRC35ZJX-S
Power supply			1Phase, 220/230/240V, 50Hz	
Cooling capacity	ISO-T1(JIS)	kW	2.5(0.9~3.2)	3.5(0.9~4.1)
Heating capacity	ISO-T1(JIS)	kW	3.4(0.9~4.7)	4.2(0.9~5.1)
Cooling input	at 230V	kW	0.58(0.19~0.82)	1.08(0.19~1.26)
Heating input	at 230V	kW	0.75(0.23~1.20)	1.10(0.23~1.43)
Cooling energy label			A	
Heating energy label			A	
EER (In cooling)			4.31	3.24
COP (In heating)			4.53	3.82
Running current	Cooling	A	2.9/2.8/2.7	5.0/4.7/4.5
	Heating	A	3.7/3.6/3.4	5.1/4.8/4.6
Sound power level *	Cooling(Indoor/Outdoor)	dB(A)	54/60	56/62
	Heating(Indoor/Outdoor)	dB(A)	55/60	57/62
Sound pressure level *	Cooling(Indoor)	dB(A)	Hi:40 Me:35 Lo:29	Hi:42 Me:37 Lo:30
	Heating(Indoor)	dB(A)	Hi:41 Me:38 Lo:31	Hi:43 Me:40 Lo:32
Air flow	Indoor	Cooling	Hi:8.5 Me:7.0 Lo:5.0	Hi:9.0 Me:7.5 Lo:5.5
		Heating	Hi:10.0 Me:9.0 Lo:6.5	Hi:11.0 Me:9.5 Lo:7.0
	Outdoor	CMM	Cooling:29.5 Heating:27.0	Cooling:32.5 Heating:29.5
Exterior dimensions (H×W×D)	Indoor	mm	230×740×455	
	Outdoor	mm	595×780(+62)×290	
Net weight	Indoor/Outdoor	kg	22/38	
Refrigerant piping	O.D	Liquid line	φ 6.35 (1/4")	
		Gas line	φ 9.52 (3/8")	
	Connecting method		Flare connecting	
Refrigerant			R410A	
Clean filter			—	

The data are measured under the following conditions(ISO-T1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

* Indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.