



PAC 4 way cassette indoor unit (FDT)

Product Code: FDT125VG



Unit details

MODEL NUMBER		FDT125VG
GRILLE		T-PSA-5AW-E
Nominal cooling	kW	12.5
Nominal heating	kW	14
Height (indoor-grille)	mm	298 (35)
Width (indoor-grille)	mm	840 (950)
Depth (indoor-grille)	mm	840 (950)
Weight (indoor-grille)	kg	30 (5)
Indoor unit airflow rate (l - m - h - ph)	l/s	300 - 417 - 467
Static pressure	Pa	0
Discharge spigots		na
Sound pressure level (l - m - h - ph)	dB(A)	32 - 39 - 41
Pipe connection size - gas	in	5/8"
Pipe connection size - liquid	in	3/8"
Drain connection	mm	VP 25 (O.D 32)
Lift pumps?		Yes, 850mm from the underside of the ceiling tile
Knock out from fresh air intake?		yes, 60 x 100
Knock out from branch duct?		yes 100 x 100
Power supply		from outdoor
Interconnecting cables		3 core + E
Controller included?		no

* exact cooling and heating capacities will depend on connected outdoor unit

Compatible outdoor units

PART NUMBER	DESCRIPTION
RC-EX1A	Touch screen wired remote controller with 7 day time clock
RC-E5	Wired remote controller with 7 day time clock
RCH-E3	Simplified wired remote controller
RCN-T-46W-E	Infra red remote controller kit
SC-ADNA-E	Superlink adapter for connection to central controllers
PCZ006A043	CNT connector for remote on/off, run/fault etc.

Compatible outdoor units

PART NUMBER	SYSTEM TYPE	OUTDOOR UNIT TYPE	POWER SUPPLY
SRC40ZMX-S	1 to 1	Hyper inverter	1Ph