

Air Conditioning

Product Information

SLZ-M R410A
600x600 4-Way Blow Ceiling Cassette System
Inverter Heat Pump

Making a
World of
Difference

Mr.SUM.



The **SLZ-M** cassette unit provides the smart solution to comfortable and efficient air conditioning. It combines a stylish square design slimline grille with the latest energy-saving technologies and is designed to fit snugly to ceilings making it ideal in both offices and retail.

Key Features

- New Design - Fits into narrow ceiling spaces with height of only 245mm
- Optional 3D i-see sensor grille provides customised comfort by automatically monitoring room occupancy, position and body temperatures
- Horizontal Airflow - eliminating uncomfortable draughts and improving airflow control



Cooling | Heating | Ventilation | Controls

Air Conditioning

Product Information

SLZ-M R410A
600x600 4-Way Blow Ceiling Cassette System
Inverter Heat Pump

Making a
World of
Difference






SLZ-M-FA INDOOR UNITS		SLZ-M15FA	SLZ-M25FA	SLZ-M35FA	SLZ-M50FA	SLZ-M60FA
CAPACITY (kW)	Heating (nominal)	1.7 (0.9-3.1)	3.2 (1.3-4.2)	4.0 (1.7-5.0)	5.0 (1.7-6.0)	6.4 (2.5-7.4)
	Cooling (nominal)	1.5 (0.9-2.4)	2.6 (1.5-3.2)	3.5 (1.4-3.9)	4.6 (2.3-5.2)	5.6 (2.3-6.5)
	Heating (UK)	-	2.69 (1.09-3.53)	3.36 (1.43-4.20)	4.20 (1.43-5.04)	5.38 (2.10-6.22)
	Cooling (UK)	-	2.60 (1.50-3.20)	3.46 (1.38-3.86)	4.56 (2.28-5.15)	5.55 (2.28-6.44)
SHF (nominal)	-	0.78	0.72	0.72	0.68	0.68
COP / EER (nominal)	-	3.61 / 3.8	3.61 / 3.60	3.61 / 3.60	3.21 / 3.30	2.81 / 3.17
SCOP / SEER (BS EN14825)	-	4.3 / 6.3	4.3 / 6.5	4.3 / 6.5	4.3 / 6.3	4.1 / 6.2
ErP ENERGY EFFICIENCY CLASS Heating/Cooling	-	A+ / A++				
AIRFLOW (l/s)	Lo-Mi1-Mi2-Hi	100-108-117	108-125-142	108-133-158	117-150-192	125-192-217
PIPE SIZE mm (in)	Gas/Liquid	9.52 (3/8")	9.52 (3/8")	9.52 (3/8")	12.7 (1/2")	15.88 (5/8")
SOUND PRESSURE LEVEL (dBA)	Lo-Mi1-Mi2-Hi	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")
SOUND POWER LEVEL (dBA)		24-26-28	25-28-31	25-30-33	27-34-39	32-40-43
DIMENSIONS (mm)	Width x Depth x Height (Grille)	45	48	51	56	60
WEIGHT (kg)	Unit / Panel	570 (650) x 570 (650) x 245 (10)	570 (650) x 570 (650) x 245 (10)	570 (650) x 570 (650) x 245 (10)	570 (650) x 570 (650) x 245 (10)	570 (650) x 570 (650) x 245 (10)
ELECTRICAL SUPPLY		15 / 3	15 / 3	15 / 3	15 / 3	15 / 3
FUSE RATING (BS88) - HRC (A)		Fed by Outdoor Unit				
INTERCONNECTING CABLE No. Cores		6	6	6	6	6
GRILLE REFERENCE		4	4	4	4	4
WIRED REMOTE CONTROLLER REFERENCE		SLP-2FA	SLP-2FA	SLP-2FA	SLP-2FA	SLP-2FA
WIRELESS REMOTE CONTROLLER REFERENCE		PAR-33MAA	PAR-33MAA	PAR-33MAA	PAR-33MAA	PAR-33MAA

Note: SLZ-M15FA only available with R32 MXZ Multi-Split outdoor units.

SUZ-KA-VA6 OUTDOOR UNITS	N/A MULTI-SPLIT ONLY	SUZ-KA25VA6	SUZ-KA35VA6	SUZ-KA50VA6	SUZ-KA60VA6
SOUND PRESSURE LEVEL (dBA) Heating/Cooling	-	48 / 47	50 / 49	52 / 52	55 / 55
SOUND POWER LEVEL (dBA) Cooling	-	58	62	65	65
WEIGHT (kg)	-	30	35	54	50
DIMENSIONS (mm) Width x Depth x Height	-	800 x 285 x 550	800 x 285 x 550	840 x 330 x 880	840 x 330 x 880
ELECTRICAL SUPPLY	-	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz
PHASE	-	Single	Single	Single	Single
SYSTEM POWER INPUT (kW) Heating/Cooling (nominal)	-	0.89 / 0.68	1.11 / 0.97	1.56 / 1.39	2.28 / 1.77
Heating/Cooling (UK)	-	0.76 / 0.58	0.94 / 0.83	1.33 / 1.20	1.94 / 1.52
STARTING CURRENT (A)	-	4.2	5.1	7.0	10.1
SYSTEM RUNNING CURRENT (A) Heating/Cooling [MAX]	-	3.2 / 4.2 (7.2)	4.5 / 5.1 (8.7)	6.3 / 7.0 (12.3)	7.8 / 10.1 (14.4)
FUSE RATING (BS88) - HRC (A)	-	10	10	20	20
MAINS CABLE No. Cores	-	3	3	3	3
MAX PIPE LENGTH (m)	-	20	20	30	30
MAX HEIGHT DIFFERENCE (m)	-	12	12	30	30
CHARGE REFRIGERANT (kg) / CO ₂ EQUIVALENT (t) R410A (GWP 2088)	-	0.80 / 1.67	1.15 / 2.40	1.60 / 3.34	1.60 / 3.34
MAX ADDITIONAL REFRIGERANT (kg) / CO ₂ EQUIVALENT (t) R410A (GWP 2088)	-	0.39 / 0.81	0.39 / 0.81	0.46 / 0.96	0.46 / 0.96

PRODUCT DIMENSIONS SLZ-M15/25/35/50/60FA



Telephone: 01707 282880
email: air.conditioning@meuk.mee.com
web: airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environment Systems Division
Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881

IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland
Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)

Country of origin: United Kingdom - Japan - Thailand - Malaysia. ©Mitsubishi Electric Europe 2018. Mitsubishi and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks or registered trademarks of their respective owners.

Note: The fuse rating is for guidance only. Please refer to the relevant databook for detailed specification. It is the responsibility of a qualified electrician/electrical engineer to select the correct cable size and fuse rating based on current regulation and site specific conditions. Mitsubishi Electric's air conditioning equipment and heat pump systems contain a fluorinated greenhouse gas, R410A (GWP:2088), R32 (GWP:675), R407C (GWP:1774) or R134a (GWP:1430). *These GWP values are based on Regulation (EU) No 517/2014 from IPCC 4th edition. In case of Regulation (EU) No.626/2011 from IPCC 3rd edition, these are as follows: R410A (GWP:1975), R32 (GWP: 550), R407C (GWP:1650) or R134a (GWP:1300).



www.greengateway.mitsubishielectric.co.uk
Mitsubishi Electric UK's commitment to the environment

Follow us @meuk_Jes
Follow us @green_gateway

Mitsubishi Electric
Living Environmental Systems UK

mitsubishielectric2

thehub.mitsubishielectric.co.uk

Effective as of April 2018