



SRK25ZS-SB

2.5kW

Specifications

Nominal cooling capacity		kW	2.5
Nominal heating capacity		kW	3.4
Sound power level	Cooling	dB(A)	52
	Heating	dB(A)	55
Sound pressure level	Cooling(Hi/Me/Lo/Ulo)	dB(A)	36 / 28 / 23 / 19
	Heating(Hi/Me/Lo/Ulo)	dB(A)	39 / 30 / 24 / 19
Air flow	Cooling(Hi/Me/Lo/Ulo)	m ³ /min	9.9 / 8.0 / 5.9 / 5.0
	Heating(Hi/Me/Lo/Ulo)	m ³ /min	11.3 / 8.7 / 6.7 / 5.9
Exterior dimensions (H×W×D)		mm	290×870×230
Net weight		kg	9.5
Refrigerant piping size	Liquid / Gas	mm ø	6.35(1/4") / 9.52(3/8")
Clean filter			Allergen Clear Filter × 1, Photocatalytic Washable Deodorizing Filter × 1

- The data is measured under the following conditions(ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.
- Sound level the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

Schematics

