



SRK35ZSX-WB

3.5kW



Specifications

Nominal cooling capacity		kW	3.5
Nominal heating capacity		kW	4.5
Sound power level	Cooling	dB(A)	58
	Heating	dB(A)	58
Sound pressure level	Cooling(Hi/Me/Lo/Ulo)	dB(A)	43 / 35 / 26 / 19
	Heating(Hi/Me/Lo/Ulo)	dB(A)	42 / 35 / 28 / 19
Air flow	Cooling(Hi/Me/Lo/Ulo)	m ³ /min	13.1 / 10.8 / 7.3 / 5.0
	Heating(Hi/Me/Lo/Ulo)	m ³ /min	13.9 / 11.8 / 8.6 / 5.4
Exterior dimensions (H×W×D)		mm	305×920×220
Net weight		kg	13.0
Refrigerant piping size	Liquid / Gas	mm ø	6.35(1/4") / 9.52(3/8")
Clean filter		Allergen Clear Filter x1, Photocatalytic Washable Deodorizing Filterx1	

- The data is measured under the following conditions(ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.
- Sound level the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

Schematics

SRK20ZSX-W, -WB, -WT SRK25ZSX-W, -WB, -WT
SRK35ZSX-W, -WB, -WT SRK50ZSX-W, -WB, -WT
SRK60ZSX-W, -WB, -WT



Space for installation and service when viewing from the front

Symbol	Content
A	Gas piping
B	Liquid piping
C	Hole on wall for right rear piping
D	Hole on wall for left rear piping
E	Drain hose
F	Outlet for piping