



SRK50ZSX-WB

5.0kW

Specifications

Nominal cooling capacity		kW	5.0
Nominal heating capacity		kW	5.8
Sound power level	Cooling	dB(A)	59
	Heating	dB(A)	62
Sound pressure level	Cooling(Hi/Me/Lo/Ulo)	dB(A)	44 / 39 / 31 / 22
	Heating(Hi/Me/Lo/Ulo)	dB(A)	46 / 41 / 33 / 23
Air flow	Cooling(Hi/Me/Lo/Ulo)	m ³ /min	14.3 / 12.4 / 7.8 / 5.4
	Heating(Hi/Me/Lo/Ulo)	m ³ /min	17.3 / 14.3 / 9.8 / 6.2
Exterior dimensions (H×W×D)		mm	305×920×220
Net weight		kg	13.0
Refrigerant piping size	Liquid / Gas	mm ø	6.35(1/4") / 12.7(1/2")
Clean filter			Allergen Clear Filter x1, Photocatalytic Washable Deodorizing Filterx1

- The data is measured under the following conditions(ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.
- Sound level the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

