



SRF25ZMX-S

2.5kW

Specifications

Nominal cooling capacity		kW	2.5
Nominal heating capacity		kW	3.4
Sound power level	Cooling	dB(A)	51
	Heating	dB(A)	51
Sound pressure level	Cooling(Hi/Me/Lo/Ulo)	dB(A)	40 / 32 / 29 / 26
	Heating(Hi/Me/Lo/Ulo)	dB(A)	40 / 35 / 33 / 28
Air flow	Cooling(Hi/Me/Lo/Ulo)	m ³ /min	9.0 / 7.6 / 6.7 / 5.8
	Heating(Hi/Me/Lo/Ulo)	m ³ /min	10.5 / 8.2 / 7.7 / 6.6
Exterior dimensions (H×W×D)		mm	600×860×238
Net weight		kg	18.0
Refrigerant piping size	Liquid / Gas	mm ø	6.35(1/4") / 9.52(3/8")
Clean filter		Allergen Clear Filter × 1 Photocatalytic Washable Deodorizing Filter×1	

- The data is measured under the following conditions(ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.
- Sound level the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

Symbol	Content
A	Gas piping
B	Model 25.35 : $\phi 9.52 (3/8")$ (Flare) 50 : $\phi 12.7 (1/2")$ (Flare)
C	Lead piping $\phi 6.35 (1/4")$ (Flare)
D	Hole on wall for right rear piping ($\phi 65$)
E	Hole on wall for left rear piping ($\phi 65$)
F	Drain hose VP16
G	Screw point fasten the indoor unit $\phi 5$
H	Outlet for piping (on both side)