

WALL MOUNTED SPECIFICATION STANDARD PLUS



LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification
: www.eurovent-certification.com



Dual Inverter
COMPRESSOR



Smart ThinQ



Embedded
Wi-Fi



Smart
Diagnosis



Active
Energy
Control



Energy
Display



Dual
Protection
Filter



Auto
Cleaning



Jet Cool



4 Way
Swing



Fast
Heating



Gold Fin™



Comfort
Air



Low Noise
19dB
(9k, 12k)



Silence
Mode



Quick
& Easy
Installation

• Single Combination

Unit				9K	12K	18K	24k
Indoor				PC09SQ.NSJ	PC12SQ.NSJ	PC18SQ.NSK	PC24SQ.NSK
Capacity	Cooling	Min/Rated/Max	W	890 / 2500 / 3700	890 / 3500 / 4040	900 / 5000 / 5500	900 / 6600 / 7420
	Heating +7°C	Min/Rated/Max	W	890 / 3300 / 4100	890 / 4000 / 5100	900 / 5800 / 6400	900 / 7500 / 8640
	Heating -7°C	Rated	W	2600	3000	4200	4850
Power Input	Cooling	Rated	W	656	1080	1562	2164
	Heating +7°C	Rated	W	800	1050	1611	2238
	Heating -7°C	Rated	W	2600	3000	4200	4850
EER			W/W	3.81	3.24	3.20	3.05
S.E.E.R.				7.0	6.6	7.0	6.9
P design C			kW	2.5	3.5	5.0	6.6
COP			W/W	4.13	3.81	3.60	3.35
S.C.O.P.				4.0	4.0	4.3	4.2
P design H			kW	2.5	2.5	3.9	5.0
Energy Label	Cooling (A++ to E Scale)			A++	A++	A++	A++
	Heating (A++ to E Scale)			A+	A+	A+	A+
Annual Energy Consumption	Cooling		kWh	125	186	250	335
	Heating		kWh	875	875	1270	1628
Sound Pressure	Cooling	S / L / M / H	dB(A)	19 / 27 / 35 / 41	19 / 27 / 35 / 41	31 / 34 / 39 / 44	31 / 34 / 42 / 47
	Heating	L / M / H	dB(A)	27 / 35 / 41	27 / 35 / 41	34 / 39 / 44	34 / 42 / 47
Sound Power	Cooling	High	dB(A)	59	59	60	65
	Heating	S / L / M / H	m³/min	3.0 / 4.2 / 7.5 / 10.0	3.0 / 4.2 / 7.5 / 10.0	8.0 / 10.5 / 13.0 / 14.5	8.0 / 10.5 / 13.1 / 16.1
Air Flow Rate	Cooling	Max (Power)	m³/min	12.5	12.5	15.5	20.0
	Heating	L / M / H	m³/min	5.6 / 7.2 / 10.0	5.6 / 7.2 / 10.0	11.0 / 13.5 / 16.0	10.5 / 13.1 / 16.1
Dehumidification Rate	Cooling	Rated	l/h	1.1	1.3	1.8	2.5
	Heating	Max	A	3.3	4.7	6.9	9.8
Running Current	Cooling	Rated	A	6.0	6.0	9.0	14.0
	Heating	Max	A	4.0	4.7	7.1	10.4
Starting Current	Cooling/Heating	Rated	A	7.0	7.0	9.5	14.0
Power Supply			Ø/V/Hz	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Circuit Breaker			A	15	15	20	25
Power Supply Cable			N x mm²	3 x 1.0	3 x 1.0	3 x 1.5	3 x 2.5
Power&TransmissionCable			N x mm²	4 x 1.0	4 x 1.0	4 x 1.0	4 x 1.0
Dimension			mm	837 x 308 x 189	837 x 308 x 189	998 x 345 x 210	998 x 345 x 210
Net Weight			kg	8.7	8.7	11.9	11.9
Fan Motor Output			W	30	30	30	60
List Price	Indoor Unit	£		£206.00	£224.00	£298.00	£399.00
Outdoor				PC09SQ.UA3	PC12SQ.UA3	PC18SQ.UL2	PC24SQ.U24
Operation Range	Cooling	Min/Max	°CDB	-10 / 48	-10 / 48	-15 / 48	-15 / 48
	Heating	Min/Max	°CDB	-10 / 24	-10 / 24	-10 / 24	-10 / 24
Sound Pressure	Cooling	High	dB(A)	48	48	53	53
	Heating	High	dB(A)	50	50	55	54
Sound Power	Cooling	High	dB(A)	65	65	65	70
	Heating	High	dB(A)	65	65	65	70
Air Flow Rate	Cooling	High	m³/min	27	27	35	50
	Heating	High	m³/min	27	27	35	50
Piping	Length(Odu/Idu)	Min/Max	m	3 / 15	3 / 15	3 / 20	3 / 30
	Elevation(Odu/Idu)	Max	m	7	7	10	15
Piping Connection	Liquid	OD(Outside)	mm(inch)	Ø 6.35 (1/4)	Ø 6.35 (1/4)	Ø 6.35 (1/4)	Ø 6.35 (1/4)
	Gas	OD(Outside)	mm(inch)	Ø 9.52 (3/8)	Ø 9.52 (3/8)	Ø 12.7 (1/2)	Ø 15.88 (5/8)
Refrigerant	Drain	OD(Outside)	mm(inch)	21.5 (0.85)	21.5 (0.85)	21.5 (0.85)	21.5 (0.85)
	Type			R32	R32	R32	R32
Charge at 7.5m	Charge at 7.5m		g	700	700	1000	1100
	t-CO ₂ eq			0.47	0.47	0.68	0.74
Additional charge	Additional charge		g/m	20	20	20	20
	GWP			675	675	675	675
Fan Motor Output			W	43	43	43	85
Compressor Type				Twin Rotary	Twin Rotary	Twin Rotary	Twin Rotary
Net Weight			kg	25.1	25.1	34.4	46.0
Dimension			mm	717 x 483 x 230	717 x 483 x 230	770 x 545 x 288	870 x 650 x 330
List Price	Outdoor Unit	£		£337.00	£382.00	£537.00	£658.00
List Price	System Price	£		£543.00	£606.00	£835.00	£1,057.00

* This product contains Fluorinated greenhouse gases (R32).

** S : Sleep / L : Low / M : Medium / H : High