



SRR60ZM-S

6.0kW

Specifications

Nominal cooling capacity		kW	6.0
Nominal heating capacity		kW	6.8
Sound power level	Cooling	dB(A)	60
	Heating	dB(A)	63
Sound pressure level	Cooling(Hi/Me/Lo/Ulo)	dB(A)	44 / 38 / 35 / 30
	Heating(Hi/Me/Lo/Ulo)	dB(A)	45 / 41 / 38 / 33
Air flow	Cooling(Hi/Me/Lo/Ulo)	m ³ /min	14.5 / 11.5 / 10.5 / 8.0
	Heating(Hi/Me/Lo/Ulo)	m ³ /min	15.0 / 13.0 / 11.5 / 9.0
Available external static pressure		Pa	50(Initial static pressure with air filter : 5Pa)
Exterior dimensions (H×W×D)		mm	200×950×500
Net weight		kg	24.0
Refrigerant piping size	Liquid / Gas	mm ø	6.35(1/4") / 12.7(1/2")
Bottom air inlet kit (option)			UT-BAT2EF

- The data is measured under the following conditions(ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.
- Sound level the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

Schematics



SRR50ZM-S SRR60ZM-S

