



TE COMPACT AND EFFICIENT

- Compact design only 799mm wide
- Wide range: 6 different capacities suit any room
- Cleaner air with PM2.5 Filter
- Quiet operation from only 20dB(A)
- New Aerowings design: twin blades for better airflow control
- · High energy savings: rated A++
- · Can reuse existing piping
- Wired control (Optional)
- Smartphone control (Optional)

This data refers to specific units in the line-up, see full leaflet for technical details of each model.



Seasonal efficiency in cooling will bring you saving all year while heating. Energy efficiency rank from A+++ to D.



Seasonal efficiency in heating will bring you saving all year while heating. Energy efficiency rank from A+++ to D.



The Inverter range provides more precise temperature control and keeps the ambient temperature constant with lower energy consumption and a significant

reduction in noise



Panasonic R2 Rotary Compressor. Designed to withstand extreme conditions, it delivers high performance and efficiency.



This filter can catch PM2,5 particles including hazardous pollutants as well as house dust and



With Super Quiet technology our devices are much more quiet than a library (30dB(A)).



More comfort with Aerowings. Direct airflow to ceiling to create shower cooling effect by twin flap built in indoor.



The Panasonic renewal system allows good quality existing R22 pipe work to be re-used whilst installing new high efficiency R410A systems.



ready to connect to internet and be managed by smartphone, with a powerful and user friendly App to manage the comfort wherever you



Ready to be integrated and be managed by centralized systems with CZ-CAPRA1





Communication port to integrate the unit to home and building management systems most known standards.




5 Years Warranty. We guarantee the outdoor unit compressors in the entire range for five years.

TE compact indoor size

At only 799mm wide, the indoor unit can be fixed in extremely small spaces - on the top of a door or other narrow spaces. The TE Inverter models are powerful and efficient, with a high energy efficiency class of A++ / A+. The TE works very efficiently in cooling mode from -10°C outdoors and -15°C in heating mode. Furthermore, the PM2.5 filter and the low operation noise makes the TE Series a great choice for projects requiring compact, efficient and quiet air conditioning.

Compact and quiet indoor unit of from 799mm wide

TE indoors are really compact. With only 799mm width, the indoor unit can be easily fixed in the space over the door.





Smartphone control and statistics

With the new accessory CZ-TACG1 control the comfort and the power consumption with your smartphone or tablet via internet. Offering even more functions as if you were at home or office: start/stop, mode operation, set temperature, room temperature, weekly timer, etc as well as the new, advanced functionality provided by Internet Control to achieve better comfort and helping to increase the efficiency. Connect the CZ-TACG1 accessory to the indoor unit and link wireless to your home internet router.




PM2,5 Filter. Particulate matter (PM2,5) can be found suspended in the air, including dust, dirt, smoke and liquid droplets. This filter can catch PM2,5 particles including hazardous pollutants as well as house dust and pollen. It is able maintain clean the air of the room by deodorization too.





Superior airflow control with Aerowings

Panasonic's Aerowings feature incorporates two independent blades that concentrate airflow to cool you down in the shortest time possible. This also helps distribute cool air evenly throughout the room and you can stay comfortable without experiencing continuous direct cooling.





Kit			KIT-TE20-TKE	KIT-TE25-TKE	KIT-TE35-TKE	KIT-TE42-TKE	KIT-TE50-TKE	KIT-TE60-TKE
Cooling capacity	Nominal (Min - Max)	kW	2,00 (0,75 - 2,40)	2,50 (0,85 - 3,00)	3,50 (0,85 - 3,90)	4,20 (0,85 - 4,60)	5,00 (0,98 - 5,60)	6,30 (0,98 - 7,10)
SEER 1)		W/W	6,10 A++	6,10 A	6,10 A	5,60 A+	6,50 A·-	6,20 A++
Input power cooling	Nominal (Min - Max)	kW	0,53 (0,25 - 0,64)	0,67 (0,25 - 0,91)	1,02 (0,26 - 1,21)	1,28 (0,27 - 1,67)	1,49 (0,29 - 1,75)	1,97 (0,28 - 2,42)
Heating capacity	Nominal (Min - Max)	kW	2,70 (0,70 - 3,60)	3,30 (0,80 - 4,10)	4,00 (0,80 - 5,10)	5,00 (0,80 - 6,80)	5,80 (0,98 - 7,80)	7,20 (0,98 - 8,50)
Heating capacity at -7°C		kW	2,14	2,70	3,30	3,90	4,66	5,24
SCOP 1)		W/W	4,00 A+	4,10 A+	4,10 △+	3,80 ◀▲	4,10 △	4,00 🔼
Input power heating	Nominal (Min - Max)	kW	0,68 (0,19 - 1,05)	0,81 (0,20 - 1,15)	1,07 (0,20 - 1,44)	1,37 (0,20 - 2,07)	1,56 (0,34 - 2,32)	2,13 (0,34 - 2,74)
Sound pressure 2)	Cool (Hi / Lo / Q-Lo)	dB(A)	37/25/20	40/26/20	42/30/20	44/31/29	44/37/34	45/37/34
	Heat (Hi / Lo / Q-Lo)	dB(A)	38/26/22	40/27/22	42/33/22	44/35/28	44/37/34	45/37/34
Indoor unit Dimension / Net weight	HxWxD	mm / kg	290 x 799 x 197 / 8	302 x 1102 x 244 / 12	302 x 1102 x 244 / 12			
Outdoor unit Dimension 3) / Net weight	HxWxD	mm / kg	542 x 780 x 289 / 26	542 x 780 x 289 / 27	542 x 780 x 289 / 32	619 x 824 x 299 / 32	619 x 824 x 299 / 40	695 x 875 x 320 / 42
Refrigerant (R410A)		kg/TCO ₂ Eq.	0,66/1,378	0,77/1,608	0,95/1,984	1,01/2,109	1,38/2,881	1,34/2,798
	HxWxD							

Accessories		Accessories			
CZ-TACG1	NEW Panasonic Wifi kit for internet control	CZ-RD514C	Wired remote controller for wall mounted		
CZ-CAPRA1	RAC interface adapter for integration into P Link				

1) Energy Label Scale from A+++ to D. 2) The sound pressure of the units shows the value measured of a position 1m in front of the main body and 0,8m below the unit. The sound pressure is measured in accordance with Eurovent 6/C/006-97 specification. Q-Lo: Quiet mode. Lo: The lowest fan speed.3) Add 70mm for piping port.

anasonic

To find out how Panasonic cares for you, log on to: www.aircon.panasonic.eu

Panasonic Marketing Europe GmbH Panasonic Air Conditioning Hagenauer Strasse 43, 65203 Wiesbaden, Germany

heating & cooling solutions