



This Wall Mounted air conditioner is especially designed for professional applications such as computer rooms where cooling inside the room is necessary even when the outside temperature is low. Furthermore this air conditioner has an automatic changeover system, in order to maintain the inside temperature even when sharp outside temperature changes occur.

Technical focus

- This units can be installed on R22 pipings
- Designed for 24h/7d a week operation

- Highly efficient even at -20°C
- High durability rolling bearings
- Additional piping sensors to prevent freezing

Outdoor Features

- Cooling even when ambient temperature is as low as -20°C
- Electronic expansion valve (accurate sub-cooling and adjustable refrigerant flow)
- Outdoor DC fan motor to provide flexible air-flow to ensure optimum condensation pressure (works on outdoor pipe temperature sensor)

Kit			KIT-E9-PKEA	KIT-E12-PKEA	KIT-E15-PKEA	KIT-E18-PKEA
Cooling capacity	Nominal (Min - Max)	kW	2.50 (0.85 - 3.00)	3.50 (0.85 - 4.00)	4.20 (0.98 - 5.00)	5.00 (0.98 - 6.00)
EER ¹⁾	Nominal (Min - Max)	W/W	4.85 (4.23 - 5.00) A	4.02 (3.57 - 5.00) A	3.50 (3.50 - 3.16) A	3.47 (3.50 - 3.02) A
Cooling capacity at -10°C / -20°C		kW	2.63 / 2.61	3.69 / 3.66	5.04 / 4.06	6.00 / 5.82
EER at -10°C / -20°C		W/W	7.19 / 6.71	5.96 / 5.56	6.01 / 4.39	6.00 / 5.39
SEER ²⁾		W/W	7.10 A++	6.70 A++	6.30 A++	6.90 A++
Pdesign		kW	2.5	3.5	4.2	5.0
Input power cooling	Nominal (Min - Max)	kW	0.52 (0.17 - 0.71)	0.87 (0.17 - 1.12)	1.20 (0.28 - 1.58)	1.44 (0.28 - 1.99)
Annual electricity consumption (cooling) ³⁾		kWh/a	123	183	233	254
Heating capacity	Nominal (Min - Max)	kW	3.40 (0.85 - 5.40)	4.00 (0.85 - 6.60)	5.40 (0.98 - 7.10)	5.80 (0.98 - 8.00)
Heating capacity at -7°C ⁴⁾		kW	3.33	4.07	4.10	4.98
COP ¹⁾	Nominal (Min - Max)	W/W	4.86 (4.12 - 5.15) A	4.35 (3.63 - 5.15) A	3.75 (2.88 - 3.24) A	3.82 (2.88 - 3.11) A
SCOP ⁵⁾		W/W	4.40 A+	4.10 A+	3.90 A	4.20 A+
Pdesign at -10°C		kW	2.8	3.6	3.6	4.4
Input power heating	Nominal (Min - Max)	kW	0.70 (0.165 - 1.31)	0.92 (0.17 - 1.82)	1.44 (0.34 - 2.19)	1.52 (0.34 - 2.57)
Annual electricity consumption (heating) ³⁾		kWh/a	891	1229	1292	1467
Indoor Unit			CS-E9PKEA	CS-E12PKEA	CS-E15PKEA	CS-E18PKEA
Power source		V	230	230	230	230
Recommended fuse		A	16	16	16	16
Connection indoor / outdoor		mm	4 x 1.5	4 x 1.5	4 x 1.5	4 x 2.5
Current	Cooling / Heating	A	2.5 / 3.3	4.0 / 4.2	5.4 / 6.5	6.4 / 6.8
Max. Current		A	7.8	8.4	9.6	11.3
Air Volume	Cooling / Heating	m³/min	13.3 / 14.6	13.6 / 14.7	14.1 / 15.0	17.9 / 19.3
Moisture removal volume		L/h	1.5	2.0	2.4	2.8
Sound pressure ⁶⁾	Cooling — Heating (Hi / Lo / S-Lo)	dB(A)	39 / 26 / 23 — 40 / 27 / 24	42 / 29 / 26 — 42 / 33 / 29	43 / 32 / 29 — 43 / 35 / 29	44 / 37 / 34 — 44 / 37 / 34
Dimensions ⁷⁾ / Net weight	H x W x D	mm / kg	295 x 870 x 255 / 10	295 x 870 x 255 / 10	295 x 870 x 255 / 10	295 x 1070 x 255 / 13
Outdoor Unit			CU-E9PKEA	CU-E12PKEA	CU-E15PKEA	CU-E18PKEA
Air Volume	Cooling / Heating	m³/min	31.3 / 29.7	32.9 / 32.1	34.2 / 33.0	39.2 / 37.9
Sound pressure ⁶⁾	Cooling / Heating (Hi)	dB(A)	46 / 47	48 / 50	46 / 46	47 / 47
Dimensions ⁷⁾ / Net weight	H x W x D	mm / kg	622 x 824 x 299 / 36	622 x 824 x 299 / 36	695 x 875 x 320 / 45	695 x 875 x 320 / 46
Piping connections	Liquid pipe / Gas pipe	Inch (mm)	1/4 (6.35) / 3/8 (9.52)	1/4 (6.35) / 3/8 (9.52)	1/4 (6.35) / 1/2 (12.70)	1/4 (6.35) / 1/2 (12.70)
Piping length range / Elevation difference (in/out) ⁸⁾		m	3 ~ 15 / 5	3 ~ 15 / 5	3 ~ 15 / 15	3 ~ 20 / 15
Pipe length for additional gas / Additional gas amount		m / g/m	7.5 / 20	7.5 / 20	7.5 / 20	7.5 / 20
Refrigerant loading		kg	1.10	1.10	1.06	1.24
Operating range	Cooling / Heating Min / Max	°C	-20 ~ +43 / -15 ~ +24	-20 ~ +43 / -15 ~ +24	-20 ~ +43 / -15 ~ +24	-20 ~ +43 / -15 ~ +24

Accessories

PAW-GRDSTD40	Outdoor elevation platform
PAW-WTRAY	Tray for condenser water compatible with base ground support
PAW-GRDBSE20	Outdoor base ground support for noise and vibration absorption

Accessories

PAW-SERVER-PKEA	PCB for installation in server rooms with security
CZ-CAPRA1	H Generation interface to ECoI control integration

Rating Conditions for cooling capacity at low temperature: Cooling Indoor 27°C DB / 19°C WB. Cooling Outdoor 0°C DB / -10°C WB.

1) EER and COP, Energy Saving Classification, is at 220 / 240V (380 / 415V) only in accordance with EU directive 2002/31/EC. 2) SEER is calculated in base Eurovent IPLV for SBEM for U1 indoor unit SEER=a(EER25)+b(EER50)+c(EER75)+d(EER100) where EER25, EER50, EER75 and EER100 are the EER measured value at 25%, 50%, 75% and 100% part load for temperatures 20, 25, 30 and 35°C DB, respectively. a, b, c and d are values assigned for an office type. These values are given as a=0.2, b=0.36, c=0.32 and d=0.03. The internal temperatures are taken at 27°C DB and 19°C WB. 3) The annual consumption (ErP) is calculated by formula determined by ErP regulation. 4) Heating capacity is calculated including defrost factor correction. 5) SCOP is calculated in base Eurovent IPLV for SBEM with U1 indoor unit including defrost correction factor. 6) The Sound pressure of the units shows the value measured of a position 1 meter in front of the main body and 1.5m from the ground. The sound pressure is measured in accordance with Eurovent 6/C/006-97 specification. 7) Add 70mm for piping port. 8) When installing the outdoor unit at a higher position than the indoor unit. // Recommended fuse for the indoor 3A.



CU-E9PKEA
CU-E12PKEA



CU-E15PKEA
CU-E18PKEA



Included wired remote
controller CZ-RD514C



SEER and SCOP: For KIT-E9-PKEA. SUPER QUIET: For KIT-E25-PKEA. INTERNET CONTROL: Optional. 5 YEARS COMPRESSOR WARRANTY: Only for PRO Partners. Compatible with all Panasonic connectivity solutions. For detailed information go to the Control Systems section.

Rating Conditions: Cooling Indoor 27°C DB / 19°C WB. Cooling Outdoor 35°C DB / 24°C WB. Heating Indoor 20°C DB. Heating Outdoor 7°C DB / 6°C WB. (DB: Dry Bulb; WB: Wet Bulb)
Specifications subject to change without notice. For detailed information about ErP, please visit our websites www.aircon.panasonic.eu or www.gtc.panasonic.eu.