

New Ceiling Model - Economy Series



Indoor unit

[Single phase] ABYG18/22/24/30/36/45KRTA
[3 phase] ABYG36/45KRTA

Outdoor unit

[Single phase] AOYG18/22/24/30/36/45KATA
[3phase] AOYG36/45KQTA



ABYG18/22KRTA



ABYG24/30KRTA




ABYG36/45/54KRTA

Point

Flexible installation

Drain hose and piping can be set in the casing and drawn out flexibly in the right, left, side and down directions.



Point

Light Elegant Design

Light-elegant and three-dimensional expression composed of curved surface gives comfort and wellbeing.



Point

Easy maintenance


The front panel can be opened without removing the whole unit for safe & speedy maintenance.



Drain pan can be taken off for cleaning.



Components in the control box can be easily accessed.



Point

Easy installation

The indoor unit can be easily installed under the ceiling due to the new designed mounting.

1. Set mounting brackets
2. Hold up the ceiling and fit the ceiling to the mounting brackets
3. Attach with screws



Point

Compact and light weight indoor unit

This model is much more compact than conventional indoor unit. Since it is lighter than the R410 model, the burden of lifting is also reduced.



Weight
-33%

(30 model)

Model: Indoor unit [Single phase] ABYG18KRTA / ABYG22KRTA / ABYG24KRTA / ABYG30KRTA / ABYG36KRTA / ABYG45KRTA
[3 phase] ABYG36KQTA / ABYG45KQTA

Outdoor unit [Single phase] AOYG18KATA / AOYG22KATA / AOYG24KATA / AOYG30KATA / AOYG36KATA / AOYG45KATA
[3 phase] AOYG36KQTA / AOYG45KQTA



ABYG18/22KRTA



ABYG24/30KRTA



ABYG36/45/54KRTA



AOYG18/22KATA



AOYG24KATA



AOYG30/36KATA
AOYG36KQTA



AOYG45KATA
AOYG45KQTA


Optional parts

Compact Remote Controller:	UTY-RCRYZ1
Wired Remote Controller : (Touch Panel)	UTY-RNRYZ3
Simple Remote Controller: (Without operation mode)	UTY-RHRY
Simple Remote Controller:	UTY-RSRY
External Switch Controller :	UTY-TERX
External input and output PCB :	UTY-XCSX
External input and output PCB Box :	UTZ-GXEA
External Connect Kit :	UTY-XWZXZG
Wireless LAN Interface:	UTY-TFSXZ1
MODBUS® Converter:	UTY-VMSX
KNX® Convertor	UTY-VKSX
Drain Pump Unit:	UTR-DPB24T
IR Receiver Unit :	UTY-LBTYH
L-Type Piping Kit:	UTP-FX24A (18/22/24) UTP-FX35A (30/36/45)
Network Convertor for single split : (DC power supply type)	UTY-VTGX
Network Convertor for single split :	UTY-VTGXV
Wireless interface for use with Smart home products: (AC power supply type)	FJ-AC-WIFI-1
(Outdoor unit 30/36/45/54)	UTY-XWZXZ3
External Connect Kit:	

Dimensions

Indoor unit : ABYG18/22/24/30/36/45/54KRTA

(Unit : mm)




	ABYG 18/22KRTA	ABYG 24/30KRTA	ABYG 36/45KRTA
A	1,080	1,390	1,700
B	923	1,233	1,543

Outdoor unit :
AOYG18/22KATA

AOYG24KATA

AOYG30/36KATA
AOYG36KQTA

AOYG45KATA
AOYG45KQTA



Economy Specifications

Model No.	Indoor unit		ABYG18KRTA	ABYG22KRTA	ABYG24KRTA	ABYG30KRTA	ABYG36KRTA	ABYG45KRTA	ABYG36KRTA	ABYG45KRTA	
	Outdoor unit		AOYG18KATA	AOYG22KATA	AOYG24KATA	AOYG30KATA	AOYG36KATA	AOYG45KATA	AOYG36KQTA	AOYG45KQTA	
Power Source			Single phase, ~230V, 50Hz						3 phase, ~400V, 50Hz		
Capacity	Cooling	kW	5.2(0.9-5.4)	6.0(0.9-6.3)	6.8(0.9-7.4)	8.5(2.8-9.6)	9.5(2.8-10.6)	12.1(4.0-12.6)	9.5(2.8-10.6)	12.1(4.0-12.6)	
	Heating		6.0(0.9-6.3)	7.0(0.9-7.4)	7.5(0.9-8.6)	10.0(2.7-10.8)	10.8(2.7-12.5)	13.5(4.2-15.0)	10.8(2.7-12.5)	13.5(4.2-15.0)	
UK Total / Sensible Cooling			5.01 / 3.62	5.85 / 4.12	6.63 / 4.97	8.08 / 5.23	9.03 / 7.44	11.54 / 8.37	9.03 / 7.44	11.54 / 8.37	
Input Power	Cooling/Heating	kW	1.66/1.71	-/-	2.19/2.00	2.78/2.86	3.13/3.03	4.84/4.18	3.13/3.03	4.84/4.18	
EER	Cooling	W/W	3.13	-	3.11	3.06	3.04	2.5	3.04	2.5	
COP	Heating		3.51	-	3.75	3.5	3.56	3.23	3.56	3.23	
Pdesign	Cooling/Heating(-10°C)	kW	5.2/3.8	6.0/4.4	6.8/5.4	8.5/8.0	9.5/8.7	12.1/9.2	9.5/-	12.1/-	
SEER	Cooling	W/W	5.8	5.6	6.0	5.8	5.6	-	5.6	-	
SCOP	Heating		3.8	3.8	3.9	3.9	3.9	-	3.9	-	
Energy Efficiency Class	Cooling	kWh/a	A+	A+	A+	A+	A+	-	A+	-	
	Heating		A	A	A	A	A	-	A	-	
Annual Energy Consumption	Cooling	kWh/a	-	-	-	-	-	-	-	-	
	Heating		-	-	-	-	-	-	-	-	
Moisture Removal			l/h		-	-	-	-	-	-	
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	38/-/-/-	42/-/-/-	41/-/-/-	45/-/-/-	44/40/37/32	45/41/39/34	44/40/37/32	45/41/39/34	
	Indoor (Heating)	H/M/L/Q	38/-/-/-	42/-/-/-	41/-/-/-	45/-/-/-	44/40/37/32	45/41/39/34	44/40/37/32	45/41/39/34	
Sound Power Level	Outdoor(Cooling/Heating)	High	51/52	52/53	54/55	53/55	55/55	58/59	55/55	58/59	
	Indoor(Cooling/Heating)	High	53/53	57/57	56/56	60/60	59/59	60/60	59/59	60/60	
Airflow Rate	Outdoor(Cooling/Heating)	High	63/64	64/65	66/67	68/69	70/70	72/73	70/70	72/73	
	Indoor / Outdoor (Cooling)	High	840/1,710	900/2,240	1,230/2,885	1,400/3,750	1,850/3,750	1,900/4,450	1,850/3,750	1,900/4,450	
	Indoor / Outdoor (Heating)	High	840/1,840	900/2,240	1,230/2,350	1,400/3,750	1,800/3,750	1,850/4,450	1,850/3,750	1,850/4,450	
Net Dimensions	Indoor	mm	235×1,080×705	235×1,080×705	235×1,390×705	235×1,390×705	235×1,700×705	235×1,700×705	235×1,700×705	235×1,700×705	
H x W x D	Outdoor	mm	542×799×290	632×799×290	632×799×290	788×940×320	788×940×320	988×940×320	788×940×320	998×940×320	
Weight	Indoor	kg(lbs)	24(53)	24(53)	31(68)	31(68)	38(84)	38(84)	38(84)	38(84)	
	Outdoor	kg(lbs)	33(73)	36(79)	38(84)	52(115)	52(115)	61(134)	53(117)	62(137)	
Remote Controller Type (NOT Supplied With Unit)			NO CONTROLLER SUPPLIED WITH THESE UNITS PLEASE ORDER SEPARATELY						3 Core +Earth		
Interconnecting Cable (Suggested cable size 2.5mm)			3 Core +Earth						3 Core +Earth		
Suggested MCB Size		Amp	16	16	20	25	25	32	16	16	
Max. Operating Current	Cooling/Heating	A	10.1/10.1	11.6/11.6	12.6/12.6	22.5/22.5	22.5/22.5	28.1/28.1	10.5/10.5	13.6/13.6	
Power Supply To			Outdoor								
Connection Pipe Diameter (Gas / Liquid)			Inch	1/2 & 1/4	1/2 & 1/4	1/2 & 1/4	5/8 & 3/8	5/8 & 3/8	5/8 & 3/8	5/8 & 3/8	
Max Pipe Length (Pre-Charge)			m	20(15)	25(15)	25(20)	30(30)	30(30)	50(30)	30(30)	50(30)
Max Height Difference			m	15	20	20	30	30	30	30	30
Refrigerant	Type		R32	R32	R32	R32	R32	R32	R32	R32	
	Charge	g	900	1100	1250	1900	1900	2700	1900	2700	
	Additional Charge	g/m	20	20	20	-	-	-	-	-	
Operation Range	Cooling	°CDB	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	
	Heating	°CDB	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-10 to 24	-15 to 24	

- Specifications and design are subject to change without notice for further improvement.
- Actual products' colors may be different from the colors shown in this printed material.

Distributed by :



ISO 9001
Certified number: 01 100 073229
Fujitsu General (Thailand) Co., Ltd.

ISO 14001
Certified number: 01 104 5245
Fujitsu General (Thailand) Co., Ltd.

FUJITSU GENERAL AIR CONDITIONING (UK) LTD
Unit 150 Centennial Park, Centennial Avenue, Elstree, Herts. WD6 3SG

www.fujitsu-general.com/uk

Tel: +44 (0)208 731 3450 Fax: +44 (0)208 731 3451

Copyright© 2020 Fujitsu General Limited. All rights reserved. 3EFNP45-2001E